

Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A control arrangement for mobile equipment comprising:

a boom pivotable by means of a boom cylinder;

a shovel pivotally mounted at the boom by means of a shovel cylinder, each of the boom and the shovel including a control unit having a pilot control device and a proportional valve for controlling the boom cylinder and the shovel cylinder; and

a valve arrangement,

whereby during lowering of the boom, a control line of the boom control unit acting in the direction of lowering may be connected with a signal line of the shovel control unit, so that the shovel may be taken into a target position with respect to the boom by means of the control pressure tapped at the boom control ~~unit~~unit,

wherein the valve arrangement is arranged between a boom connecting line connected with the control line and a shovel connecting line connected with an inlet of a shuttle valve, and

wherein the shuttle valve is connected by another inlet with the signal line and by its outlet with a control chamber of the shovel proportional valve.

2. (Canceled)

3. (Currently Amended) ~~The control arrangement in accordance with claim 1, A~~
control arrangement for mobile equipment comprising:

a boom pivotable by means of a boom cylinder;

a shovel pivotally mounted at the boom by means of a shovel cylinder, each of
the boom and the shovel including a control unit having a pilot control device and a
proportional valve for controlling the boom cylinder and the shovel cylinder; and
a valve arrangement,

whereby during lowering of the boom, a control line of the boom control unit
acting in the direction of lowering may be connected with a signal line of the shovel control
unit, so that the shovel may be taken into a target position with respect to the boom by means
of the control pressure tapped at the boom control unit, and

wherein the valve arrangement includes a switching valve which is spring-biased in its basic position and has a switching solenoid which may be energized by means of an activation switch in an electric circuit.

4. (Original) The control arrangement in accordance with claim 3, wherein a position transmitter is arranged in the electric circuit which interrupts the latter as soon as the target position of the shovel is reached.

5. (Currently Amended) ~~The control arrangement in accordance with claim 1,~~ A control arrangement for mobile equipment comprising:

a boom pivotable by means of a boom cylinder;
a shovel pivotally mounted at the boom by means of a shovel cylinder, each of
the boom and the shovel including a control unit having a pilot control device and a
proportional valve for controlling the boom cylinder and the shovel cylinder; and
a valve arrangement,

whereby during lowering of the boom, a control line of the boom control unit
acting in the direction of lowering may be connected with a signal line of the shovel control
unit, so that the shovel may be taken into a target position with respect to the boom by means
of the control pressure tapped at the boom control unit, and

wherein a boom control lever of the boom pilot control device of the boom control unit is adapted to be locked in its end positions.

6. (Previously Presented) The control arrangement in accordance with claim 2, wherein the valve arrangement includes a switching valve which is spring-biased in its basic position and has a switching solenoid which may be energized by means of an activation switch in an electric circuit.

7. (Previously Presented) The control arrangement in accordance with claim 2, wherein a boom control lever of the boom pilot control device of the boom control unit is adapted to be locked in its end positions.

8. (Previously Presented) The control arrangement in accordance with claim 3, wherein a boom control lever of the boom pilot control device of the boom control unit is adapted to be locked in its end positions.

9. (Previously Presented) The control arrangement in accordance with claim 4, wherein a boom control lever of the boom pilot control device of the boom control unit is adapted to be locked in its end positions.

10. (Previously Presented) The control arrangement in accordance with claim 6, wherein a boom control lever of the boom pilot control device of the boom control unit is adapted to be locked in its end positions.

11. (Previously Presented) The control arrangement in accordance with claim 1, wherein the mobile equipment is a wheel loader or a backhoe loader.